


# GIVE YOURSELF A REAL LIFT

## CACTUS GRABS FOR CONTINUOUS LOADING OPERATIONS

Terex Fuchs Cactus Grabs are specially designed for scrap handling. With their robust design, they are suitable for tough, day-to-day operations. The superior performance of Terex Fuchs Cactus Grabs is the result of advanced kinematic design, with high tine-closing forces and a power flow perfectly matching the design. The use of high-quality materials also ensures long life. ▶ The grab rotator is an integral part of the upper grab section. ▶ Easily serviced. ▶ Pressure-relief valve protection of tine-closing cylinders. ▶ Cylinder rods and hydraulic lines protected against external damage. Tine-tips made of wear-resistant, high-manganese steel. ▶ All areas of the grab shells subject to wear are made of HARDOX steel.



### Machine type

| Machine type         | Grab type | Capacity grab open    | Height grab closed | Height of grab | Opening width | Weight* open tines | Weight* half-shell tines |
|----------------------|-----------|-----------------------|--------------------|----------------|---------------|--------------------|--------------------------|
| MHL 320/331          | 5-tine    | 0.5 yd <sup>3</sup>   | 80 in              | 93 in          | 80 in         | 2,998 lbs          | 3,219 lbs                |
|                      | 5-tine    | (0.4 m <sup>3</sup> ) | (2,020 mm)         | (2,350 mm)     | (2,030 mm)    | (1,360 kg)         | (1,460 kg)               |
| MHL 340/350/360      | 5-tine    | 0.8 yd <sup>3</sup>   | 81 in              | 98 in          | 93 in         | 3,285 lbs          | 3,549 lbs                |
|                      | 5-tine    | (0.6 m <sup>3</sup> ) | (2,050 mm)         | (2,500 mm)     | (2,360 mm)    | (1,490 kg)         | (1,610 kg)               |
| MHL 350/360          | 5-tine    | 1.0 yd <sup>3</sup>   | 83 in              | 105 in         | 99 in         | 3,329 lbs          | 3,880 lbs                |
|                      | 5-tine    | (0.8 m <sup>3</sup> ) | (2,100 mm)         | (2,600 mm)     | (2,520 mm)    | (1,510 kg)         | (1,760 kg)               |
| MHL 360 (16.5 m)/380 | 5-tine    | 1.3 yd <sup>3</sup>   | 105 in             | 121 in         | 101 in        | 5,241 lbs          | 5,732 lbs                |
|                      | 5-tine    | (1.0 m <sup>3</sup> ) | (2,655 mm)         | (3,075 mm)     | (2,560 mm)    | (2,400 kg)         | (2,600 kg)               |
| MHL 380              | 5-tine    | 1.6 yd <sup>3</sup>   | 107 in             | 125 in         | 108 in        | 5,445 lbs          | 5,952 lbs                |
|                      | 5-tine    | (1.2 m <sup>3</sup> ) | (2,710 mm)         | (3,170 mm)     | (2,740 mm)    | (2,470 kg)         | (2,700 kg)               |
| MHL 380              | 5-tine    | 1.8 yd <sup>3</sup>   | 108 in             | 128 in         | 114 in        | 5,732 lbs          | 6,283 lbs                |
|                      | 5-tine    | (1.4 m <sup>3</sup> ) | (2,745 mm)         | (3,255 mm)     | (2,900 mm)    | (2,600 kg)         | (2,850 kg)               |